



Superior Solutions



Windshield de-icer

- ICE MELT is a quality blend of the finest ice melting ingredients available today.
- Quick melting and non-smearing.
- Contains rust inhibitor.
- Especially formulated for removing frost and hard ice from vehicle windshields.
- Convenient: Ready-to-use aerosol form makes ICE MELT easy to use.
- Harmless to metal, rubber, plastic, glass, painted surfaces, cloth and clothing.
- Quickly removes ice and frost from windscreens, windows, mirrors, locks, valves, pipes, lamps and brake linkages.
- ICE MELT works quickly and effectively. Saves the time and trouble of window scraping.
- ICE MELT leaves no smeary residue to foul wiper blades and blur vision.

APPLICATIONS

ICE MELT can be used to remove frost and ice from car and truck windshields and headlights, as well as office, store and home windows. ICE MELT can also be used to thaw frozen doors, windows, and locks.

DIRECTIONS

Shake well.

FROST REMOVAL

Spray ICE MELT liberally over frosted areas on windshields, windows, or lights. Use wipers for faster action on windshields.

ICE REMOVAL

Score iced areas with a scraper and spray ICE MELT liberally over scored ice. Scrape away ice when loose.

FROZEN LOCKS

Direct spray into key opening of lock and apply liberally. Weekly application will prevent freezing.

CONDITIONS FOR USE

See the precautions for use listed on the packaging.

SPECIFICATIONS

Physical form: Aerosol

Net volume: 600 ml

Shelf Life: 1 year minimum

Storage Temperature: -18° to 54°C

Flammability: Flammable

All information in this document is based on our practical experience and/or laboratory tests. Due to the large spectrum of circumstances for usage and unpredictable human factors, we recommend that you always test our products before final usage. This technical data sheet has perhaps already been revised based on legislation, availability of the individual ingredients or newly acquired information. We can send you upon request the latest valid version, which is at the same time the sole valid version.

Version 0176-0413